

1.0 cfm portable now with password protection

Model 3313/3315 Portable Airborne Particle Counters

FEATURES

- Long Life Laser technology for superior performance
- AC or battery operation
- 0.3 micron at 1.0 cfm (3313)
- 0.5 micron at 1.0 cfm (3315)
- 3-hour battery operation
- 6 particle size channels
- Supports 21 CFR Part 11 compliance
- ISO 14644-1 calculations
- Fed-Std-209E calculations
- Stores 2000 records

APPLICATIONS

- Monitor and verify cleanrooms
- Test filters
- Track down particle sources
- Monitor:
 - Laminar Air Flow cabinets
 - Paint spray booths
 - Food Processing Areas
 - Hospital Pharmacies
 - HVAC systems
 - Indoor Air Quality
 - Aerospace Assembly
 - Medical Device Assembly
 - Cleanroom Laundries



Met One's Model 3313 and Model 3315 deliver a 1.0 cfm (28.3 L/min) sampling rate with either 0.3 micron sensitivity (3313) or 0.5 micron sensitivity (3315). Operating from either AC or batteries, the Model 3300 series can provide continuous monitoring of clean areas, storing up to 2000 readings in its memory buffer. The stored data can be reviewed on the front panel, printed or downloaded to a computer. The built-in printer is standard. The password protection of data in the Model 3300 series supports 21 CFR Part 11 compliance.

All six channels on the front panel simultaneously display optional environmental sensor data, such as relative humidity, temperature or air velocity. Alarms can be set for all measurements. Review stored records by using the scrollable display.

Both ISO 14644-1 and Federal Standard 209E calculation modes are included, allowing stored data to be analyzed according to either standard. Breakthrough Long Life Laser technology extends the average service life of the instrumentation's laser to more than ten years.

The enclosure can be either aluminum for lightness (less than 16 pounds or 8 kilograms) or stainless steel for environmental and chemical compatibility.

The Model 3313 and Model 3315 are full-featured 1.0 cfm airborne counters that offers one important difference – portability as a battery-operated instrument. With the Model 3300 series, you can “cut the cord” without losing features!

Model 3313/3315 Airborne Particle Counters

SPECIFICATIONS

Size Channels (μm)	3313	0.3, 0.5, 1.0, 3.0, 5.0, 10.0
	3315	0.5, 1.0, 2.0, 3.0, 5.0, 10.0
Flow Rate	1.0 cfm (28.3 L/min)	
Zero Count	1 count or less in 5 minutes	
Coincidence Loss	Less than 5% at 400,000 particles/ft ³	
Counting Efficiency	50% for 0.3 μm (3313); 50% for 0.5 μm (3315)	
Light Source	Laser diode (10-year MTTF)	
Pump Type	Air vacuum, rated for continuous use	
Count Display	LCD	
Maximum Count	9,999,999 displayed	
Sample/Hold Times	1 second to 24 hours	
Count Alarms	1 to 9,999,999 counts	
Count Cycles	Up to 100 while in automatic mode	
Location Labels	0 to 999, appears on printout	
Data Storage	2,000 samples, scrollable on front panel	
Outputs	RS-232/RS-485 serial interface	
Battery Type	Rechargeable NiMH	
Operating Time (Battery)	3 hours continuous	
Battery Recharge Time	2 hours 90%, 4 hours 100%	
Power	90 to 260 VAC, 50/60 Hz	
Size	13.0" w x 6.5" h x 14.0" d (33.0 x 16.5 x 35.6 cm)	
Weight	Aluminum	15.6 lbs (7.1 kg)
	Stainless Steel	22.8 lbs (10.4 kg)
Environment Operating	55 to 84°F (12 to 29°C)	
	10 to 85% relative humidity, non-condensing	
Storage	-40 to 122°F (-40 to 50°C), up to 98% relative humidity, non-condensing	
Accessories Included	Isokinetic Probe (direct mount), Isokinetic Probe with Tripod, Purge Filter, US and DIN Power Cords, Printer Paper, Manual	

ORDERING GUIDE

When ordering, specify:	
Basic Sensitivity	0.3 μm (3313) or 0.5 μm (3315)
Enclosure Type	Aluminum or stainless steel
Size Range Option (BS 5295)	0.3, 0.5, 1.0, 5.0, 10.0, 25.0

OPTIONAL ACCESSORIES

Relative Humidity/Temperature Sensor
 Air Velocity Sensor
 High Pressure Diffuser
 Isodiluter™, 10x or 50x
 Filter Scanning Probe, non-electronic
 Particle Vision® PortAll™ Software
 Carrying/Shipping Case

